



DECLARATION OF PERFORMANCE

DoP Nr. KEW - 1109-CPD-0073 - en

1. Unique identification code of the product-type: Hammer fixing DSH K

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-14/0129 Annex A2
Batch number: see packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

generic type	Plastic nailed-in anchor for fixing of external thermal insulation composite systems with rendering
for use in	Reinforced or unreinforced normal weight concrete of strength class C12/15 at minimum and C50/60 at maximum and masonry
option / category	A, B, C, D, E
loading	The anchor is to be used only as multiple fixing for the anchorage of bonded thermal insulation composite systems
material	polypropylene polyamid glass fibre covered sizes: ø10x90 - 10x190
temperature range (if applicable)	ETA-14/0129 point B2

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

KEW Kunststoffzeugnisse GmbH Wilthen
Dresdener Straße 19
02681 Wilthen
Germany

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

--

6. System or systems of assessment and verification of constancy of performance of the construction

product as set out in Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

--

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment:

Technical and Test Institute for Construction, Prague

has been issued:

ETA-14/0129

14.10.2014

on the basis of:

ETAG 014, Edition February 2011

The notified body

1109-CPD

performed

System 2+

- i) initial inspection of factory and of factory production control
- ii) continuous surveillance, assessment and approval of factory production control.

and the following is displayed:

1109-CPD-0073

9. Declared performance:

Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
		plastic	
Characteristic resistance	ETAG 014	ETA-14/0129 Annex C1	ETAG 014
Minimum edge distance and anchor spacing	ETAG 014	ETA-14/0129 Annex B4	
Displacement behavior	ETAG 014	ETA-14/0129 Annex C1	
Point thermal transmittance according	ETAG 014	ETA-14/0129 Annex C2	
Plate stiffness according	ETAG 014	ETA-14/0129 Annex C2	


Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies:

--

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:


André Gedan
 (managing director sales & marketing)
 Wilthen, 14.10.2014

