



## DECLARATION OF PERFORMANCE

DoP Nr. KEW - 1488-CPD-0097/W - en

1. Unique identification code of the product-type Injection Resin VM V
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):  
ETA-08/0089 Annex 2  
Batch number: see packaging
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

generic type	Bonded anchor with anchor rod
for use in	reinforced or unreinforced normal weight concrete of strength classes C20/25 at minimum and C50/60 at maximum
option / category	7
loading	static or quasi-static
material	2-component resin based mortar on vinyl ester basis  Steel, galvanized  covered sizes: M10, M12, M16  Stainless steel  covered sizes: M10, M12, M16
temperature range (if applicable)	ETA-08/0089 point 1.2 and 4.3

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

KEW Kunststoffzeugnisse GmbH Wilthen  
Dresdener Straße 19  
02681 Wilthen  
Germany

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

--

6. System or systems of assessment and verification of constancy of performance of the

construction product as set out in Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

--

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment:

DIBt Deutsches Institut für Bautechnik

has been issued:

ETA-08/0089

on the basis of:

ETAG 001

The notified body

1488-CPD

performed

System 1

- i) initial type-testing of the product;
- ii) initial inspection of factory and of factory production control;
- iii) continuous surveillance, assessment and approval of factory production control.

and the following is displayed:

1488-CPD-0097/W

9. Declared performance:

Essential Characteristics	Design Method	Performance		Harmonized Technical Specification
		Steel electro-galvanized	stainless steel	
Characteristic values for tension loads	ETAG 001 Anhang C	ETA-08/0089 Annex 4	ETA-08/0089 Annex 4	ETAG 001
Displacements under tension loads	ETAG 001 Anhang C	ETA-08/0089 Annex 4	ETA-08/0089 Annex 4	
Characteristic values for shear loads	ETAG 001 Anhang C	ETA-08/0089 Annex 5	ETA-08/0089 Annex 5	
Displacements under shear loads	ETAG 001 Anhang C	ETA-08/0089 Annex 5	ETA-08/0089 Annex 5	
Minimum edge distance and anchor spacing	ETAG 001 Anhang C	ETA-08/0089 Annex 3	ETA-08/0089 Annex 3	

Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies:

--

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

  
**André Gedan**  
 (managing director sales & marketing)  
 Wilthen, 27.06.2013

